


SCHATTELLO TECHNICAL DATA

Round




		Ø 4.0 m	Ø 5.0 m	Ø 6.0 m	Ø 6.0 m	
Segments		8	8	8	12	
Area	m ²	12	19	27	28	
A	Height closed incl. top plate	cm	410	425	440	450
B	Height opened incl. top plate	cm	303	318	333	343
C	Headroom with valance	cm	205	205	200	205
D	Headroom without valance	cm	227	227	222	237
E	Height of valance	cm	28	28	28	28
F	Ground clearance from spoke edge	cm	193	158	123	132
G	Height of lower disc flange	cm	183	198	213	223
Weight without packaging MayTex-Acryl without valance	kg	27	38	45	52	
Support pole diameter	mm	outer-Ø 76, pole thickness 3				
Packaging cardboard sleeve length 444 cm		Ø 33 cm approx. 17 kg		Ø 35 cm approx. 18 kg		
Installation base length/width/min. depth	cm	50/ 50/ 60		60/ 60/ 60		
Minimum-ballast Number of layers of concrete slabs X250 required		1 x = approx. 112 kg		2 x = approx. 224 kg		

Triangular



		4 x 4 x 4 m	6 x 6 x 6 m	
Segments		6	6	
Area	m ²	6.9	15.6	
A	Height closed incl. top plate	cm	391	402
B	Height opened incl. top plate	cm	284	295
C	Headroom with valance	cm	215	215
D	Headroom without valance	cm	237	237
E	Height of valance	cm	28	28
F	Ground clearance from spoke edge	cm	153	51
G	Height of lower disc flange	cm	234	183
Weight without packaging MayTex-Acryl without valance	kg	27	40	
Support pole diameter	mm	outer-Ø 76, pole thickness 3		
Packaging cardboard sleeve length 444 cm		Ø 33 cm approx. 17 kg		
Installation base length/width/min. depth	cm	50/ 50/ 60		
Minimum-ballast Number of layers of concrete slabs X250 required		1 x = approx. 112 kg		

Square




		3.0 x 3.0 m	3.5 x 3.5 m	4.0 x 4.0 m	4.5 x 4.5 m	5.0 x 5.0 m	
Segments		8	8	8	8	8	
Area	m ²	9	12,25	16	20,25	25	
A	Height closed incl. top plate	cm	410	418	425	433	440
B	Height opened incl. top plate	cm	300	308	315	323	330
C	Headroom with valance	cm	215	215	215	215	215
D	Headroom without valance	cm	237	237	237	237	237
E	Height of valance	cm	28	28	28	28	28
F	Ground clearance from spoke edge	cm	180	154	119	96	62
G	Height of lower disc flange	cm	252	190	198	203	213
Weight without packaging MayTex-Acryl without valance	kg	25	34	43	52	58	
Support pole diameter	mm	outer-Ø 76, pole thickness 3					
Packaging cardboard sleeve length 444 cm		Ø 33 cm approx. 17 kg					
Installation base length/width/min. depth	cm	50/ 50/ 60			60/ 60/ 60		
Minimum-ballast Number of layers of concrete slabs X250 required		1 x = approx. 112 kg			2 x = approx. 224 kg		

The heights specified are for parasols with MayTex-Acryl covering fabric that are mounted in an anchor tube (S2118, S2146, S2150). The increase in height for parasols with other installation bases can be seen in the list below:

Full frame pedestal:	S2201 +14 cm
Full frame pedestal:	S2203 +17 cm
Full frame pedestal:	S2205 +21 cm
Full frame pedestal:	S2411 + 9 cm
Full frame pedestal:	S2412 +12 cm
Full frame pedestal:	S2414 +16 cm
Full frame pedestal:	S2420 +19 cm
Anchor plate:	S2131 +1,5 cm
Anchor plate:	S2261 + 5 cm
Base plate:	S2272 + 4 cm
Base plate:	S2273 + 4 cm
Base plate:	S2274 + 4 cm
Base plate:	S2275 + 4 cm

3D view of installation base with top plate for winter protection. Base must be frost-proof and enlarged if the ground is unstable.



Intermediate and special sizes on request.
Dimensional tolerance approx. 5%.