



STRONGWIND PARASOL FABRICS 2026

01








Sunacryl Fabric Collection

23 solution-dyed acrylic colours for demanding outdoor environments

SUNACRYL® OUTDOOR FIBRE

100% solution-dyed acrylic | 290 g/m² ±5% | 120 cm width ±5% | Cleangard water- and stain-resistant finish

AVAILABLE FABRIC COLOURS

			
Ecrú ORC 0001 120 RAL 9003*	Naturel ORC 7133 120 RAL 9001*	Ble ORC 6318 120 RAL 1017*	Ivoire ORC 7548 120 RAL 1015*
			
Pierre ORC 6196 120 RAL 7047*	Dune ORC 0681 120 RAL 1001*	Marron ORC 0613 120 RAL 8011*	Bordeaux ORC 8206 120 RAL 3005*
			
Jaune ORC 6316 120 RAL 1003*	Orange ORC 0018 120 RAL 2004*	Vermillon ORC 0020 120 RAL 3020*	Rouge ORC 3914 120 RAL 3003*
			
Granny Chine ORC U321 120 RAL 6025*	Vert ORC 0003 120 RAL 6029*	Foret ORC 6687 120 RAL 6005*	Olive Chine ORC U814 120 RAL 6020*
			
Turquoise ORC 6688 120 RAL 6034*	Saphir ORC 6720 120 RAL 5024*	Bleu ORC 0017 120 RAL 5017*	Ocean ORC 7264 120 RAL 5002*
			
Marine ORC 6022 120 RAL 5013*	Ardoise ORC 8203 120 RAL 7012*	Noir ORC 6028 120 RAL 9011*	

* Nearest RAL reference only; colours do not have an exact RAL match.



STRONG WIND PARASOL FABRICS 2026

02

Performance & Technical Detail

Sunacryl outdoor fabric engineered for lasting colour, comfort and resilience

LIFE COMFORT BY DICKSON

Performance classes according to EN 14500 and EN 14501; measurements by the accredited CSTC/WTCB laboratory.

OUTDOOR SOLAR FACTOR Class 2-4	GLARE CONTROL Class 0-4	UV FILTRATION 90-100%	RAL GUIDE Nearest reference*
-----------------------------------	----------------------------	--------------------------	---------------------------------

PERFORMANCE BENEFITS

- UV, heat and light protection
- Breathable
- Fade resistant
- Tear resistant
- Stain resistant
- Mould resistant
- Easy care

reserved. Product photography, technical information, dimensional data and written content may not be copied, reproduced or distributed without prior written permission from Morton Parasols.

TECHNICAL CHARACTERISTICS

Material base	100% solution-dyed acrylic, Sunacryl fibre for outdoor use
Width	120 cm ±5%
Weight	290 g/m² ±5%
Finish	Cleangard anti-staining and water-resistant treatment
Water pressure	350 mm minimum - ISO 811/81
UV colour fastness	7 to 8/8 - ISO 105-B02/94
Weather resistance	4 to 5/5 - ISO 105-B04/94
Spray test	4 to 5/5 minimum - ISO 4920/81
Tensile strength	Warp 140 daN Weft 90 daN
Tear strength	Warp 4 daN Weft 2.3 daN

DURABLE BY DESIGN

Solution-dyed acrylic carries colour deep into the fibre for lasting resistance to rain and UV exposure. The water- and dirt-repellent finish helps reduce mould, while the dyeing process reduces water, energy and chemical consumption.